

LIQUID CORROSION PREVENTATIVE

NO. 50 RUST INHIBITOR

PREMIUM RUST
INHIBITOR

DESCRIPTION

This proprietary water soluble corrosion inhibiting product is designed especially for ferrous metal surfaces. It is non-flammable and readily goes into solution. It is ideal for use in spray washer systems as a final rinse or for soak tank applications.

DIRECTIONS

Soak: Charge 3 to 4 ounces per gallon of water into clean tank. Dip clean parts into solution and allow adequate contact time. Remove parts and allow excess to drain back into tank. Then allow parts to air dry and store indoors.

Spray Washer: Contact your sales representative regarding this and other applications. General use dilutions range from 1/2 to 4 oz. per gallon.

SAFETY

KEEP OUT OF REACH OF CHILDREN. Contains alkaline rust inhibitors. Eye and skin irritation hazard. Harmful if swallowed. Avoid excessive skin contact. Wear suitable protective gloves and clothing to prevent exposure. Consult the MSDS before using this product.

In case of ingestion, drink 1 or 2 glasses of water or milk. Induce vomiting by taking 2 tablespoons of syrup of ipecac. Get medical attention immediately. **In case of eye contact,** flush with running water for 15 minutes. Flush the areas behind the eyelids completely. Get immediate medical attention. **In case of skin contact,** flush with large amounts of water. Get immediate medical attention if irritation occurs. Remove and launder contaminated clothing.

DATA

APPEARANCE: Thin Green Liquid	ODOR: Bland
WETTING ABILITY: Good	FOAMING PROPERTIES: Low
RINSABILITY: Excellent	SOLUBILITY: Complete, in water
WATER HARDNESS TOLERANCE: Good	PHOSPHATES: None
pH: 8.5	DENSITY: 9.63 lbs./gal.
SPECIFIC GRAVITY: 1.155	BIODEGRADABLE: Yes
STABILITY: Excellent	

HMIS CHEMICAL CLASSIFICATION CODES: Health = 2, Fire = 0, Reactivity = 1